

Moore 352 Single-Loop Digital Controller Model Selection

	Model No. 3 5 2						
Type							
Basic	B						
Expanded	E						
Power Requirement							
120 Vac (+10%, -15%) 47 to 63 Hz (see note 1)	A						
24 Vac (+10%, -15%) 47 to 63 Hz	B						
24 Vdc (+20%, -15%)	C						
220/240 Vac (+10%, -15%) 47 to 63 Hz (see note 1)	E						
*Note 1: On newer models the "E" is no longer available. It is merged with "A"; 120/240 VAC (85 to 264 VAC) 47 to 63 Hz. Please specify your power input requirement.							
Mounting Case							
Screw Terminals, 20		1					
Screw Terminals, 40 (Required on 352E)		2					
Not Required		N					
Operators Panel							
Analog and Digital Displays			1				
Not Required			N				
Delete Panel			D				
Input Number 3 - Options							
Voltage (Additional 1 to 5 Vdc)				V			
Thermocouple (J, K, T, E, S, R, B) and Millivolt				T			
Hi Common Mode Thermocouple (J, K, T, E, S, R, B) and Millivolt				H			
RTD (DIN curve; US curve)				D			
Frequency				F			
Computer (Dual Pulse and Pulse Direction)				C			
Smart Transmitter Interface Board				M			
Not Required				N			
Link Interface							
RS422, Half-Duplex					1		
Not Required					N		
Electrical Classification							
CSA							C
FM							F
Not Required							N
	Model No. 3 5 2						
	Example: 3 5 2	B	A	1	1	V	1 F

Please let us know the exact model you require. We can often customize units for your specific needs.



Classic Automation LLC
 800 Salt Road
 Webster, NY 14580
 USA

www.classicautomation.com
 +1 (585) 241-6010

customerservice@classicautomation.com